SE-CLEAN Antistatic Products Maintenance Kit

Cleaning fluid and nylon brush for FÖGE antistatic bars, blowers, airguns and nozzles



KEY DATA

Kit contents
Antistatic products maintenance liquid (bottle with spray head) + nylon cleaning brush

Cleaning fluid
Non-conductive, water-free · solvent mixture, contains isoparaffins · free from halogenated and aromatic hydrocarbons · evaporates without residue · use undiluted

Brush dimensions
225 × 35 × 22 mm

Compatible products
FÖGE AC and DC antistatic bars, air blowers, antistatic air guns and other antistatic devices

Overview

Antistatic devices must be cleaned regularly to keep their efficiency. The strong electric field attracts airborne dust and contaminants, the ionization of the air causes carbon to build up on the electrodes, and in textile applications ink or fibres can contaminate the pins. Dirty emitter pins reduce efficiency and can cause circuit overload and short circuits.

Key features

- Non-conductive, water-free cleaning fluid — evaporates without residue
- Removes dust, carbon deposits, ink and fabric residue from emitter pins
- Nylon brush, 225 × 35 × 22 mm — cleans gently without damaging the pins
- Spray head for direct application
- For FÖGE AC and DC bars, blowers, airguns and nozzles

Technical specifications

Kit contents	Antistatic products maintenance liquid (bottle with spray head) + nylon cleaning brush
Cleaning fluid	Non-conductive, water-free · solvent mixture, contains isoparaffins · free from halogenated and aromatic hydrocarbons · evaporates without residue · use undiluted
Brush dimensions	225 × 35 × 22 mm
Brush filaments	Nylon, ⌀ 0.35 mm, 20 mm depth
Compatible products	FÖGE AC and DC antistatic bars, air blowers, antistatic air guns and other antistatic devices
Personal protection	Safety glasses · protective gloves

Hazard statements	H304: May be fatal if swallowed and enters airways · H413: May cause long lasting harmful effects to aquatic life · EUH066: Repeated exposure may cause skin dryness or cracking
Precautionary statements	P273 · P301 + P310 · P331 · P405 · P501

Usage instructions

⚠ Switch the electrode OFF and do not switch it ON again until it is dry.

1. Clean the static control device with the FÖGE cleaning brush.
2. Attach the spray head to the bottle containing the cleaning fluid.
3. Moisten a cloth with cleaning fluid and wipe the static control device, taking care around the emitters.
4. Repeat brushing and cleaning until the static control device is clean.
5. Polish the pins carefully with a dry cloth.

Complete system — what you need

SE-CLEAN kit	One bottle of cleaning fluid with spray head and one nylon cleaning brush
Replacement fluid and brushes	Available separately — contact FÖGE

Product information and ordering: sales@fogegmbh.com · +49 9372 9809477 · foge-antistatic.com